MODELS: Piper Glider TG-8 (Army TG-8, Navy XLNP-1), 3 PCLM

T.C. NUMBER: GTC 10 (Approved 8/19/42)

Type	Class II				
Airspeed limits	Glide or dive - 122 mph True Ind.				
-	Airplane tow - 122 mph True Ind.				
	Spoilers open - 122 mph True Ind.				
	Auto-winch tow - Not authorized				
C.G. range	(+13.5) to (+22.5)				
Datum	Leading edge of wing				
Leveling means	Lugs at sliding window on left longeron				
Maximum weight	1160 lbs.				
Number seats	3 (1 at (+9), 1 at (+36), and pilot at (-26))				
	(See NOTE 1.)				
Maximum baggage	20 lbs. (+49)				
Control surface	Elevator Up 34 degrees Down 29 deg	rees			
movement	Aileron Up 18 degrees Down 18 dec				
	Rudder Right 30 degrees Left 30 dec				
	Stabilizer Up 2.5 degrees Down 4 degr				
	Spoilers Up 50 degrees Down 0 degr				
Serial numbers eligible	G-1 and up (See NOTE A)				
Required equipment	Items 101, 102 and 103				

SPECIFICATIONS PERTINENT TO ALL MODELS:

Glider Type Certificate No. 10 (CAR 5) None (See NOTE A) Certification basis Production basis

ECUIPMENT:

Landing G	ear			
102.	8.00-4 (Hayes 841) wheels with tires and expander tube brakes	32	1bs.	(+3)
103.	6x2.00 steerable tail wheel (Scott Aviation Corp. Model CST-12) with	32	IDS.	(+3)
	solid tire	7	lbs.	(+193)
Electrica	1 Equipment			
301.	Battery - Reading 324LD (with box)	16	lbs.	(+20)
302.	Position lights	3	lbs.	(+79)
Interior	Equipment			
101.	Airspeed indicator	1	1b.	(-44)
303.	Extra instruments			` '
	(a) Front instrument panel	1.5	lbs.	(-44)
	(b) Middle instrument panel	2.5	lbs.	(-9) '
304.	Parachutes			• •
	(a) Front seat	20	lbs.	(-26)
	(b) Middle seat	20	lbs.	(+9)
	(c) Rear seat	20	lbs.	(+36)

- NOTE A. Each glider manufactured for civil use subsequent to 3/20/45 must,
 - prior to original certification, satisfactorily pass:

 (a) An inspection for workmanship, materials and conformity before any covering or final finish is applied. All woodwork may be varnished.

 (b) A final inspection of the completed glider.

 (c) A check of flight characteristics.
- The following placards must be installed in full view of the pilot: "Solo flight from front seat only. NOTE 1.
 - (1) Minimum weight pilot and chute 145 lbs."
 "2nd person must use middle seat."
 "Auto-winch tow prohibited."
 "Instrument flight prohibited."

 - (3)
 - (4)
- NOTE 2. Army TG-8 gliders having serial numbers G-1 and up are eligible for certification as J3 series airplanes under the provisions of the pertinent Aircraft Specifications, provided they are converted to J3 series airplanes and are in conformity with the approved Piper data. Conversion procedure is given in Safety Regulation Release No. 186.